



- NOTES:**
- 1). THE WORK SHALL CONSIST OF INSTALLING A SANDBAG DIKE FOR THE PURPOSE OF EROSION CONTROL WHEN CONSTRUCTION ACTIVITIES TAKE PLACE WITHIN THE STREAM CHANNEL SUCH AS BANK STABILIZATION OR BRIDGE ABUTMENT CONSTRUCTION.
 - 2). THE SANDBAG DIKE SHALL BE INSTALLED AT THE UPSTREAM LOCATION FIRST.
 - 3). THE DIKE SHALL BE INSTALLED TO THE TOP OF BANK, OR EQUAL WITH THE TOP OF BANK, WHICHEVER IS LESS. SEE PLANS FOR INFORMATION.
 - 4). THE SPILLWAY SHALL BE SIZED TO PASS A (1) ONE YEAR STORM EVENT PEAK FLOW, SEE PLANS.
 - 5). THE PIPE, WHEN UTILIZED, SHALL BE SIZED TO PASS THE STREAM BASE FLOW.

PLAN SYMBOL



DELAWARE
DEPARTMENT OF TRANSPORTATION

SANDBAG DIKE			
STANDARD NO.	E-20 (98)	SHT. 1	OF 1

APPROVED	_____	_____
	<small>CHIEF ENGINEER</small>	<small>DATE</small>
RECOMMENDED	_____	_____
	<small>DESIGN ENGINEER</small>	<small>DATE</small>