


CUT SECTION

BREAK IN CROSS SLOPE MAY BE ELIMINATED TO DIRECT SURFACE FLOW LEFT OR RIGHT OR AS DIRECTED BY THE ENGINEER.



FILL SECTION

- NOTES:**
- 1.) EDGE BERMS AND TEMPORARY SLOPE DRAINS SHALL BE CONSTRUCTED ALONG THE TOP OF ALL SLOPES TO INTERCEPT RUNOFF AND CONVEY IT DOWN THE SLOPE FACES WITHOUT CREATING GULLIES OR WASHOUTS.
 - 2.) SLOPE FACES SHALL BE TRACKED WITH CLEATED EQUIPMENT SUCH THAT THE CLEAT MARKS ARE ORIENTED HORIZONTALLY.
 - 3.) ALL CUT AND FILL SLOPES OF THE HIGHWAY EMBANKMENT SHALL BE PERMANENTLY STABILIZED AS THE WORK PROGRESSES IN INCREMENTS NOT TO EXCEED 10' (3000) MEASURED ALONG THE SLOPE.
 - 4.) CROSS SLOPES SHALL BE 2% MINIMUM, 6% MAXIMUM.




**DELAWARE
DEPARTMENT OF TRANSPORTATION**

INCREMENTAL STABILIZATION


STANDARD NO. E-1 (2001) SHT. 1 OF 1

APPROVED *Ryan M. Harkness* 6/18/01
CHIEF ENGINEER DATE

RECOMMENDED *Michael P. Gotsch* 6/18/01
DESIGN ENGINEER DATE




ISOMETRIC VIEW



SECTION A-A


- NOTES:**
- 1). THIS DEVICE IS INTENDED TO CONTROL SHEET FLOW ONLY. IT SHALL NOT BE USED IN AREAS OF CONCENTRATED FLOW.
 - 2). SILT FENCE ENDS SHALL BE TURNED UPSLOPE TO CONTAIN RUNOFF.
 - 3). REINFORCING STRIP IS TO BE ONE COMPLETE STRIP COVERING ALL GEOTEXTILE FABRIC AT POST.




SECTION B-B

ELEVATION




WIRE MESH DETAIL
(REINFORCED SILT FENCE ONLY)




UNREINFORCED SILT FENCE
CONNECTON DETAIL




REINFORCED SILT FENCE
CONNECTON DETAIL

| | | | | |
|--|---------------------------------------|----------------------|--------------------|--|
|  DELAWARE DEPARTMENT OF TRANSPORTATION | SILT FENCE | | | APPROVED  10/10/06 |
| | STANDARD NO. E-2 (2006) | SHT. 1 | OF 1 | RECOMMENDED  10/13/06 |



ISOMETRIC VIEW



SECTION A-A





DELAWARE
DEPARTMENT OF TRANSPORTATION

DRAINAGE INLET SEDIMENT CONTROL


STANDARD NO. E-3 (2005)

SHT. 1 OF 1

APPROVED *Carolann Wick* 12/5/05
CHIEF ENGINEER DATE
RECOMMENDED *James M. O'Brien* 11/29/05
DESIGN ENGINEER DATE






SECTION A-A




PLAN


NOTES:

- 1). FOR DITCHES LESS THAN 30" (750) IN DEPTH, PLACE DAM AS DIRECTED BY THE ENGINEER.
- 2). THE CHECK DAM HEIGHT MUST NOT EXCEED 2' (600) AT THE CENTER OF THE WEIR.
- 3). THE CHECK DAM IS TO BE CONSTRUCTED SO THAT THE CENTER IS 6" (150) MIN. LOWER THAN THE OUTER EDGES, FORMING A WEIR THAT WATER CAN FLOW ACROSS.
- 4). GEOTEXTILE FABRIC IS TO BE INSTALLED UNDERNEATH RIPRAP ON PERMANENT CHECK DAMS ONLY.
- 5). THE MAXIMUM SPACING BETWEEN DAMS SHALL BE THE DISTANCE IN THE DITCH WHERE THE TOE OF THE UPSTREAM DAM IS AT THE SAME ELEVATION AS THE TOP OF THE DOWNSTREAM DAM AT THE CENTER OF THE WEIR.


| | | | | |
|--|-------------------------|--------|------|---|
|  DELAWARE DEPARTMENT OF TRANSPORTATION | STONE CHECK DAM | | | APPROVED  <u>10/10/06</u> CHIEF ENGINEER DATE |
| | STANDARD NO. E-5 (2006) | SHT. 1 | OF 1 | RECOMMENDED  <u>10/13/06</u> DESIGN ENGINEER DATE |



PLAN



SECTION A-A





SECTION B-B

- NOTES:**
- 1). SEDIMENT TRAPS ARE INTENDED FOR USE IN EXISTING, PROPOSED, AND TEMPORARY DITCHES OF ALL TYPES WITH A MAXIMUM DRAINAGE AREA OF 15 ACRES (6 HECTARES), AS SHOWN ON PLANS OR AS DIRECTED BY THE ENGINEER.
 - 2). SIDE SLOPES SHALL BE STABILIZED WITH "TEMPORARY GRASS SEEDING, DRY GROUND" AND STRAW MULCH.
 - 3). AN OUTLET STRUCTURE IS REQUIRED. STONE CHECK DAMS, PERFORATED RISER PIPES, SKIMMER DEWATERING DEVICES, OR DRAINAGE INLETS MAY BE USED. SEE APPROPRIATE STANDARD SHEET FOR ADDITIONAL INFORMATION.
 - 4). FOR SIZE, LOCATION, ETC. OF SEDIMENT TRAP, SEE CONSTRUCTION PHASING, M.O.T., AND EROSION CONTROL PLANS.
 - 5). ALL FILL SLOPES SHALL BE 2:1.
 - 6). A 2:1 LENGTH TO WIDTH RATIO SHOULD BE ACHIEVED WHERE POSSIBLE. IF THIS IS NOT POSSIBLE, THE USE OF BAFFLES OR OTHER SPECIAL DESIGNS SHOULD BE INCORPORATED TO INCREASE FLOW TIME.




DELAWARE
DEPARTMENT OF TRANSPORTATION

| SEDIMENT TRAP | | | | APPROVED <i>Carolann Wick</i> CHIEF ENGINEER | 12/5/05 DATE |
|---------------|------------|------|--------|--|------------------|
| STANDARD NO. | E-6 (2005) | SHT. | 1 OF 1 | RECOMMENDED <i>James M. O'Brien</i> DESIGN ENGINEER | 11/29/05 DATE |




- NOTES:**
- 1). THE WORK SHALL CONSIST OF THE CONSTRUCTION OF A SEDIMENT TRAP AROUND A DRAINAGE INLET TO ALLOW SEDIMENTATION TO OCCUR BEFORE RUNOFF ENTERS THE DRAINAGE INLET.
 - 2). DRAINAGE INLET SEDIMENT TRAPS SHALL BE LIMITED TO A THREE (3) ACRE (1.2 HECTRARE) MAXIMUM DRAINAGE AREA.
 - 3). THE DIMENSIONS OF THE DRAINAGE INLET SEDIMENT TRAP ARE TO BE AS INDICATED ON THE PLANS OR AS DIRECTED BY THE ENGINEER.

| | | | | |
|--|---|--------|------|--|
|  DELAWARE DEPARTMENT OF TRANSPORTATION | SEDIMENT TRAP, USING DRAINAGE INLET AS OUTLET | | | APPROVED <i>Carolann Wick</i> 12/5/05 CHIEF ENGINEER DATE |
| | STANDARD NO. E-7 (2005) | SHT. 1 | OF 1 | RECOMMENDED <i>James M. O'Brien</i> 11/29/05 DESIGN ENGINEER DATE |

| MIN. * OUTFALL PIPE DIA. | MIN. RISER DIA. | MAX. DRAINAGE AREA ACRES (ha) |
|--------------------------------|--------------------|-------------------------------------|
| 12" (300) | 15" (375) | 1 (0.4) |
| 15" (375) | 18" (450) | 2 (0.8) |
| 18" (450) | 21" (525) | 3 (1.2) |
| 21" (525) | 24" (600) | 4 (1.6) |
| 24" (600) | 27" (675) | 5 (2.0) |

* OUTFALL PIPE DIAMETER MAY BE SAME SIZE AS RISER DIAMETER.



ELEVATION

- NOTES:
- 1). THIS DEVICE IS INTENDED TO BE USED AS AN OUTLET FOR SEDIMENT TRAPS.
 - 2). THE PIPE OUTLET SHOWN SHALL BE USED WITH SEDIMENT TRAPS WITH DRAINAGE AREAS OF 5 ACRES (2.0 HECTARES) OR LESS. LARGER DRAINAGE AREAS REQUIRE AN ENGINEERED DESIGN.
 - 3). THE HEIGHT OF THE SKIMMER DEWATERING DEVICE SHALL BE SPECIFIED BY THE ENGINEER IN THE FIELD.



DELAWARE
DEPARTMENT OF TRANSPORTATION

RISER PIPE ASSEMBLY FOR SEDIMENT TRAP

STANDARD NO. E-8 (2006)

SHT. 1 OF 2

APPROVED


Frank Taylor
CHIEF ENGINEER

10/10/06
DATE


RECOMMENDED

Dan Smith
DESIGN ENGINEER

10/13/06
DATE




PLAN



FRONT

| TRASH HOOD CHART | | | | | |
|---------------------|------------|-----------|--------------------------|--------------------------|---------------------------|
| RISER PIPE DIAMETER | D | H | TRASH HOOD THICK. (GAGE) | MINIMUM SIZE SUPPORT BAR | MINIMUM TOP THICK. (GAGE) |
| 15" (375) | 21" (525) | 7" (175) | 16 (1.6) | *6 (*19) REBAR | 16 (1.6) |
| 18" (450) | 27" (675) | 8" (200) | 16 (1.6) | *6 (*19) REBAR | 16 (1.6) |
| 21" (525) | 30" (750) | 11" (275) | 16 (1.6) | *6 (*19) REBAR | 16 (1.6) |
| 24" (600) | 36" (900) | 13" (330) | 16 (1.6) | *6 (*19) REBAR | 14 (2.0) |
| 27" (675) | 42" (1050) | 15" (380) | 16 (1.6) | *6 (*19) REBAR | 14 (2.0) |
| 36" (900) | 54" (1350) | 17" (430) | 14 (2.0) | *8 (*25) REBAR | 12 (2.7) |



ISOMETRIC VIEW

TRASH HOOD DETAILS



DELAWARE
DEPARTMENT OF TRANSPORTATION

RISER PIPE ASSEMBLY FOR SEDIMENT TRAP

STANDARD NO. E-8 (2006)

SHT. 2 OF 2

APPROVED


Frank Taylor
CHIEF ENGINEER

10/10/06
DATE

RECOMMENDED


Don Smith
DESIGN ENGINEER

10/13/06
DATE




STABILIZATION OF EMBANKMENTS

- NOTES:**
1. STAPLES TO BE STAGGERED AT 18" (450) SPACING.
 2. TOPSOIL UNDER EROSION CONTROL BLANKET IS TO BE TRACKED AND SEEDED.
 3. WHEN OFFSITE RUNOFF OCCURS, ADDITIONAL MEASURES AS DIRECTED BY THE ENGINEER SHALL BE USED TO ENSURE STABILITY OF EMBANKMENT.




STAPLE DETAIL




OVERLAP DETAIL

STAPLES TO BE STAGGERED AT 6" (150) SPACING.




INITIAL TRENCH ANCHOR DETAIL

APPLIED AT THE DOWNSTREAM END OF DITCH




TERMINAL TRENCH ANCHOR DETAIL

APPLIED AT THE UPSTREAM END OF DITCH



**STABILIZATION OF DITCHES
PLAN**

- NOTES:**
1. ADDITIONAL STAPLES NOT SHOWN ARE REQUIRED AT OVERLAPS. SEE OVERLAP DETAIL FOR STAPLE PLACEMENT.
 2. STAPLES ARE TO BE STAGGERED.
 3. TOPSOIL UNDER EROSION CONTROL BLANKET IS TO BE TRACKED AND SEEDED.



**STABILIZATION OF DITCHES
SECTION A-A**

STAPLES ALONG LONGITUDINAL EDGES SHALL BE SPACED AS FOLLOWS:
18" (450) WHEN SL ≤ 20' (6000)
9" (225) WHEN SL > 20' (6000)




DELAWARE
DEPARTMENT OF TRANSPORTATION


EROSION CONTROL BLANKET APPLICATIONS

STANDARD NO. E-9 (2005) SHT. 1 OF 1


APPROVED *Carolann Wick* 12/5/05
CHIEF ENGINEER DATE
RECOMMENDED *James M. O'Brien* 11/29/05
DESIGN ENGINEER DATE





SECTION A-A



SECTION B-B



PLAN



SECTION DETAILS

CLASS RIPRAP

- R-4 d = 14" (350) MIN.
- R-5 d = 26" (650) MIN.
- R-6 d = 34" (850) MIN.

- NOTES:**
- 1). SECURING PINS ARE TO BE PLACED AT LOCATIONS SHOWN AND AT 24" (600) LONGITUDINAL AND LATERAL SPACING.
 - 2). SEE PLANS FOR LOCATION, DIMENSIONS, GRADES, ETC.
 - 3). USE OF R-7 RIPRAP WILL REQUIRE A SEPARATE PROFESSIONAL ENGINEERING DESIGN FOR SIGHT SPECIFIC CONDITIONS.



**DELAWARE
DEPARTMENT OF TRANSPORTATION**

RIPRAP DITCH

STANDARD NO.

E-10 (2005)

SHT. 1

OF 1

APPROVED


Carolann Wick
CHIEF ENGINEER

12/5/05
DATE

RECOMMENDED


James M. O'Brien
DESIGN ENGINEER

11/29/05
DATE



SECTION A-A

| CHART A - STABILIZATION | | | |
|-------------------------|-------------|---|--|
| SYMBOL | SWALE GRADE | TYPE OF TREATMENT | |
| | | DRAINAGE AREA A (5 AC (2 ha) OR LESS) | DRAINAGE AREA B (5 AC - 10 AC (2 ha - 4 ha)) |
| 1 | 0.5-2.0% | SEED USED WITH EROSION CONTROL BLANKET | SEED USED WITH EROSION CONTROL BL. |
| 2 | 2.1-8.0% | R-4 RIRRAP | R-4 RIRRAP |
| 3 | 8.1-20% | ENGINEERED DESIGN | ENGINEERED DESIGN |




PLAN

| CHART B - SWALE DIMENSIONS | | |
|----------------------------|----------------|----------------|
| SYMBOL | SWALE A | SWALE B |
| C | 1' (300) MIN. | 1' (300) MIN. |
| D | 4' (1200) MIN. | 6' (1800) MIN. |

SEE SECTION A - A


- NOTES:**
- 1). DIVERTED RUNOFF FROM A DISTURBED AREA SHALL BE CONVEYED TO A SEDIMENT TRAPPING DEVICE.
 - 2). DIVERTED RUNOFF FROM AN UNDISTURBED AREA SHALL OUTLET DIRECTLY INTO AN UNDISTURBED STABILIZED AREA AT NON-EROSIVE VELOCITY.
 - 3). IF TEMPORARY SWALES OR CLEAN WATER DIVERSIONS ARE TO BE OPERATIONAL FOR MORE THAN 14 DAYS, THEY SHALL BE STABILIZED IN ACCORDANCE WITH CHART A PRIOR TO BECOMING OPERATIONAL.
 - 4). IF TEMPORARY SWALES OR CLEAN WATER DIVERSIONS ARE TO BE OPERATIONAL FOR LESS THAN 14 DAYS, THEY SHALL BE STABILIZED WITH GEOTEXTILE IN ACCORDANCE WITH THE STANDARD DETAIL, "GEOTEXTILE-LINED CHANNEL DIVERSION".



SECTION A-A


| CHART A - SWALE STABILIZATION | | |
|-------------------------------|-------------|----------------------------------|
| SYMBOL | SWALE GRADE | TYPE OF TREATMENT |
| A-1 | 0.5-2.0% | SEED AND EROSION CONTROL BLANKET |
| A-2 | 2.1-8.0% | LINED R-4 RIPRAP |
| A-3 | 8.1-20% | ENGINEERED DESIGN |

MAXIMUM DRAINAGE AREA: 2 ACRES (0.8 ha)




PLAN

- NOTES:**
- 1). DIVERTED RUNOFF FROM A DISTURBED AREA SHALL BE CONVEYED TO A SEDIMENT TRAPPING DEVICE.
 - 2). DIVERTED RUNOFF FROM AN UNDISTURBED AREA SHALL OUTLET INTO AN UNDISTURBED STABILIZED AREA AT NON-EROSIVE VELOCITY.
 - 3). IF PERIMETER DIKE SWALES ARE TO BE OPERATIONAL FOR MORE THAN 14 DAYS, THEY SHALL BE STABILIZED IN ACCORDANCE WITH CHART A PRIOR TO BECOMING OPERATIONAL.
 - 4). IF TEMPORARY SWALES OR CLEAN WATER DIVERSIONS ARE TO BE OPERATIONAL FOR LESS THAN 14 DAYS, THEY SHALL BE STABILIZED WITH GEOTEXTILE IN ACCORDANCE WITH THE STANDARD DETAIL, "GEOTEXTILE-LINED CHANNEL DIVERSION".



| CHART A - FLOW CHANNEL STABILIZATION | | |
|--------------------------------------|---------------|----------------------------------|
| TYPE | CHANNEL GRADE | TYPE OF TREATMENT |
| 1 | 0.5-2.0% | SEED AND EROSION CONTROL BLANKET |
| 2 | 2.1-8.0% | R-4 RIPRAP |
| 3 | 8.1-20% | ENGINEERED DESIGN |




SECTION A-A




| CHART B - EARTH DIKE DIMENSIONS | | |
|---------------------------------|---------------------------------|----------------------------|
| SYMBOL | DIKE A (5 ac (2 ha) or less) | DIKE B (5-10ac(2-4 ha)) |
| a-DIKE HEIGHT | 12" (300) | 18" (450) |
| b-DIKE WIDTH | 12" (300) | 24" (600) |
| c-FLOW WIDTH | 48" (1200) | 72" (1800) |
| d-FLOW DEPTH | 14" (350) | 27" (680) |

- NOTES:
- 1). IF DESIRED, TOP WIDTH MAY BE WIDER AND SIDE SLOPES MAY BE FLATTER TO FACILITATE CROSSING BY CONSTRUCTION TRAFFIC.
 - 2). FIELD LOCATION SHOULD BE ADJUSTED AS NEEDED TO INSURE A STABILIZED OUTFALL.

SCALE : N.T.S.



ANTI-SEEP COLLAR



- NOTES:** 1). ALL TEMPORARY SLOPE DRAINS SHALL DISCHARGE INTO THE BACK OF SEDIMENT TRAPS, INTO SEDIMENT BASINS OR DITCHES DISCHARGING INTO TRAPS OR BASINS.
- 2). TEMPORARY SLOPE DRAINS SHALL BE USED AT THE TOP OF FILL SLOPES AS EMBANKMENT IS CONSTRUCTED, TO PREVENT EXCESSIVE EROSION UNTIL SHOULDERS ARE CONSTRUCTED AND THE SLOPES ARE SEEDED AND MULCHED.




DELAWARE
DEPARTMENT OF TRANSPORTATION

TEMPORARY SLOPE DRAIN

STANDARD NO. E-14 (2005) SHT. 1 OF 1

APPROVED *Carolann Wick* 12/5/05
CHIEF ENGINEER DATE
RECOMMENDED *James M. O'Brien* 11/29/05
DESIGN ENGINEER DATE



- NOTES:**
- 1). THE WORK SHALL CONSIST OF CONSTRUCTING A STILLING WELL FOR THE PURPOSE OF PUMPING CLEAN WATER AROUND A DISTURBED CONSTRUCTION AREA TO A STABILIZED OUTFALL.
 - 2). THE DIMENSIONS OF THE STILLING WELL SHALL BE AS SHOWN ON THE PLANS OR AS DIRECTED BY THE ENGINEER.



DELAWARE
DEPARTMENT OF TRANSPORTATION

STILLING WELL

STANDARD NO.

E-15 (2005)

SHT. 1

OF 1

APPROVED


Carolann Wick
CHIEF ENGINEER

12/5/05
DATE


RECOMMENDED

James M. O'Brien
DESIGN ENGINEER

11/29/05
DATE



PLAN



SECTION A-A

- NOTES:**
- 1). THE WORK SHALL CONSIST OF CONSTRUCTING A SUMP PIT FOR THE PURPOSE OF FILTERING AND PUMPING WATER TO A STABILIZED OUTFALL.
 - 2). GEOTEXTILE FOR THE 36" (900) CMP SHALL BE REPLACED WHEN CLOGGED WITH SEDIMENT.
 - 3). $\frac{1}{2}$ " x $\frac{1}{2}$ " (13 x 13) 19 GAGE (1.1) WIRE MESH SHALL BE PLACED AROUND THE REMOVABLE 36" (900) CMP BEFORE ATTACHING THE GEOTEXTILE TO INCREASE FLOW THROUGH THE GEOTEXTILE.
 - 4). ALL PERFORATIONS SHALL BE 1" (25) IN DIAMETER AND 12" (300) ON CENTER IN ALL DIRECTIONS.
 - 5). TYPE I SUMP PIT SHALL BE USED ONLY WHEN PUMPING IS NEEDED FOR LESS THAN 7 DAYS.

| SUMP PIT CHART | | | | |
|----------------|---|---|----------------|-----------|
| TYPE | PIPE 1 | PIPE 2 | A | B |
| 1 | PERFORATED 24" (600) CMP WITH PERFORATED CAP WELDED ON BOTTOM AND COMPLETELY WRAPPED WITH GEOTEXTILE. | N/A | 4' (1200) MIN. | 12" (300) |
| 2 | PERFORATED 48" (1200) CMP WITH PERFORATED CAP WELDED ON BOTTOM | REMOVABLE PERFORATED 36" (900) CMP WITH PERFORATED CAP WELDED ON BOTTOM AND COMPLETELY WRAPPED WITH GEOTEXTILE. | 8' (2400) MIN. | 24" (600) |



DELAWARE
DEPARTMENT OF TRANSPORTATION

SUMP PIT, TYPE 1 & 2

STANDARD NO.

E-16 (2005)

SHT. 1

OF 1

APPROVED




Carolann Wick
CHIEF ENGINEER

12/5/05
DATE

RECOMMENDED

James M. O'Brien
DESIGN ENGINEER

11/29/05
DATE



- NOTES:**
- 1.) A DEWATERING BASIN (DWB) IS USED TO REMOVE SEDIMENT FROM SEDIMENT-LADEN WATER PUMPED FROM A CONSTRUCTION SITE BEFORE THE WATER RE-ENTERS THE WATERWAY. THE DWB SHALL HAVE A MINIMUM TOP WIDTH OF 15' (4570) AND A MINIMUM DEPTH OF 3.5' (1065). THE MINIMUM TOP LENGTH SHOWN IN THE PLAN IS USED ONLY FOR QUANTITY CALCULATIONS BY THE ENGINEER. THE ACTUAL TOP LENGTH IN THE FIELD SHALL BE CALCULATED BY THE EQUATION:
 US CUSTOMARY : TOP LENGTH (FEET) = 26' + .01 x Y
 METRIC : TOP LENGTH (mm) = 7930 + 48300 x Y
 WHERE Y IS THE MAXIMUM CAPACITY IN GALLONS PER MINUTE (CUBIC METERS PER SECOND) OF THE DEWATERING PUMP.
 - 2.) THE OUTFALL FROM THE BASIN TO THE RECEIVING WATERS SHALL BE STABILIZED. PUMPING INTO THE DWB SHALL CEASE WHEN THE EFFLUENT FROM THE BASIN BECOMES SEDIMENT-LADEN.
 - 3.) A SUMP PIT OR STILLING WELL (SEE STANDARD SHEETS) SHALL BE USED IN CONJUNCTION WITH A DWB. THE BASIN MAY BE BYPASSED INTO THE STABILIZED OUTFALL IF THE WATER BEING PUMPED IS NON-SEDIMENT-LADEN. DIRECT DISCHARGE TO THE RECEIVING WATERS SHALL CEASE AND BE REDIRECTED TO THE DWB WHEN EFFLUENT FROM THE PUMP BECOMES SEDIMENT-LADEN.
 - 4.) MAINTENANCE MUST BE PERFORMED IN ORDER FOR THE DWB TO FUNCTION PROPERLY. ACCUMULATED SEDIMENT SHALL BE REMOVED AND DISPOSED OF IN AN APPROVED DISPOSAL AREA WHEN THE BASIN IS FILLED TO WITHIN 12" (300) FROM THE CREST.
 - 5.) WHEN USED IN CONJUNCTION WITH A COFFERDAM, DEWATERING SHALL BEGIN NO SOONER THAN 12 HOURS AFTER COFFERDAM INSTALLATION IN ORDER TO ALLOW SEDIMENT PRODUCED DURING INSTALLATION TO SETTLE COMPLETELY.




DELAWARE
DEPARTMENT OF TRANSPORTATION

DEWATERING BASIN


STANDARD NO. E-17 (2005)

SHT. 1 OF 1


APPROVED *Carolann Wick* 12/15/05
 CHIEF ENGINEER DATE
 RECOMMENDED *James M. O'Brien* 11/29/05
 DESIGN ENGINEER DATE




OBLIQUE VIEW




PLAN



FASTENING DETAIL





TRENCHING DETAIL




SECTION A-A

NOTE: SEE PLANS FOR LOCATION, DIMENSIONS, GRADES, ETC.

| | | | | |
|--|------------------------------------|--------|------|--|
|  DELAWARE DEPARTMENT OF TRANSPORTATION | GEOTEXTILE-LINED CHANNEL DIVERSION | | | APPROVED <i>Carolann Wick</i> 12/5/05 CHIEF ENGINEER DATE |
| | STANDARD NO. E-18 (2005) | SHT. 1 | OF 1 | RECOMMENDED <i>James M. O'Brien</i> 11/29/05 DESIGN ENGINEER DATE |



PLAN



SECTION A-A


- NOTES:**
- 1). THE WORK SHALL CONSIST OF INSTALLING FLOW DIVERSIONS FOR THE PURPOSE OF EROSION CONTROL WHEN CONSTRUCTION ACTIVITIES TAKE PLACE WITHIN THE STREAM CHANNEL SUCH AS BANK STABILIZATION OR BRIDGE ABUTMENT CONSTRUCTION.
 - 2). THE DIVERSION STRUCTURE SHALL BE INSTALLED FROM UPSTREAM TO DOWNSTREAM.
 - 3). THE EFFECTIVE CHANNEL WIDTH SHALL BE SIZED TO PASS A ONE YEAR STORM EVENT PEAK FLOW, OR 1/3 OF STREAM WIDTH, WHICHEVER IS GREATER.
 - 4). THE SANDBAG DIVERSION HEIGHT (H) SHALL BE 1' (300) ABOVE THE PEAK ELEVATION OF THE ONE YEAR STORM.



DELAWARE
DEPARTMENT OF TRANSPORTATION

| SANDBAG DIVERSION | | | |
|-------------------|-------------|------|--------|
| STANDARD NO. | E-19 (2005) | SHT. | 1 OF 1 |

| | | |
|-------------|-------------------------|----------|
| APPROVED | <i>Carolann Wick</i> | 12/5/05 |
| | CHIEF ENGINEER | DATE |
| RECOMMENDED | <i>James M. O'Brien</i> | 11/29/05 |
| | DESIGN ENGINEER | DATE |




- NOTES:**
- 1). THE WORK SHALL CONSIST OF INSTALLING A SANDBAG DIKE FOR THE PURPOSE OF EROSION CONTROL WHEN CONSTRUCTION ACTIVITIES TAKE PLACE WITHIN THE STREAM CHANNEL SUCH AS BANK STABILIZATION OR BRIDGE ABUTMENT CONSTRUCTION.
 - 2). THE SANDBAG DIKE SHALL BE INSTALLED AT THE UPSTREAM LOCATION FIRST.
 - 3). THE HEIGHT OF THE SANDBAG DIKE SHALL BE 1' (300) ABOVE THE PEAK ELEVATION OF THE ONE YEAR STORM, OR EQUAL WITH THE TOP OF BANK, WHICHEVER IS LESS. SEE PLANS FOR INFORMATION.
 - 4). THE SPILLWAY SHALL BE SIZED TO PASS A (1) ONE YEAR STORM EVENT PEAK FLOW, SEE PLANS.
 - 5). THE PIPE, WHEN UTILIZED, SHALL BE SIZED TO PASS THE STREAM BASE FLOW.




DELAWARE
DEPARTMENT OF TRANSPORTATION


| SANDBAG DIKE | | | |
|--------------|-------------|------|--------|
| STANDARD NO. | E-20 (2005) | SHT. | 1 OF 1 |

APPROVED *Carolann Wick* 12/5/05
CHIEF ENGINEER DATE
RECOMMENDED *James M. O'Brien* 11/29/05
DESIGN ENGINEER DATE



- NOTES:**
- 1). ALL SURFACE WATER FLOWING OR DIVERTED TOWARD CONSTRUCTION ENTRANCES SHALL BE PIPED UNDER THE ENTRANCE. IF NECESSARY, A MOUNTABLE BERM WITH 5:1 SLOPES SHALL BE ALLOWED TO FACILITATE PLACEMENT OF PIPES IN SHALLOW CONDITIONS.
 - 2). THE LOCATION AND NUMBER OF STABILIZED CONSTRUCTION ENTRANCES SHALL BE AS INDICATED ON THE PLANS. ANY CHANGE IN LOCATION, ADDITION, OR DELETION OF AN ENTRANCE SHALL BE APPROVED IN ADVANCE BY THE ENGINEER.
 - 3). DRAINAGE PIPE, IF UTILIZED, SHALL BE PAID FOR SEPARATELY UNDER THE APPROPRIATE BID ITEM.
 - 4). THE TOP 2" (50) OF STONE SHALL BE REMOVED AND REPLACED WITH 2" (50) OF CLEAN STONE WHEN VOIDS ARE FILLED OR AS DIRECTED BY THE ENGINEER.






| | | | | |
|--|----------------------------------|--------|------|--|
|  DELAWARE DEPARTMENT OF TRANSPORTATION | STABILIZED CONSTRUCTION ENTRANCE | | | APPROVED <i>Carolann Wick</i> 12/5/05 CHIEF ENGINEER DATE |
| | STANDARD NO. E-21 (2005) | SHT. 1 | OF 1 | RECOMMENDED <i>James M. O'Brien</i> 11/29/05 DESIGN ENGINEER DATE |

NOTES:

- 1). ALL P.V.C. PIPES ARE TO BE 4" I.D., SCHEDULE 40.
- 2). ALL JOINTS OF THE FLOATATION SECTION SHALL BE SOLVENT WELDED.
- 3). 4" HDPE FLEXIBLE DRAIN PIPE IS TO BE ATTACHED TO THE POND OUTLET STRUCTURE WITH WATER TIGHT CONNECTIONS

SCALE : NTS



DELAWARE
DEPARTMENT OF TRANSPORTATION

SKIMMER DEWATERING DEVICE

STANDARD NO.

E-22 (2012)

SHT. 1

OF 1

APPROVED


SIGNATURE ON FILE
CHIEF ENGINEER

01/07/2013
DATE


RECOMMENDED

SIGNATURE ON FILE
DESIGN ENGINEER


12/20/2012
DATE



PLAN VIEW
OPEN WATER APPLICATION



ELEVATION



PLAN VIEW
SHORELINE APPLICATION

FLOATING TURBIDITY CURTAIN


- NOTE:** 1.) ADDITIONAL PANEL REQUIRED FOR DEPTHS GREATER THAN 5' (1500).
2.) FLOATING TURBIDITY CURTAIN SHALL REACH BOTTOM UP TO DEPTHS OF 10' (3000) BY USING TWO PANELS. DEPTHS GREATER THAN 10' (3000) SHALL REQUIRE SPECIAL DEPTH CURTAINS SPECIFICALLY CALLED FOR IN THE PLANS OR AS DIRECTED BY THE ENGINEER.




DELAWARE
DEPARTMENT OF TRANSPORTATION

| TURBIDITY CURTAIN | | | |
|-------------------|-------------|------|--------|
| STANDARD NO. | E-23 (2005) | SHT. | 1 OF 2 |


| | | |
|-------------|-------------------------|----------|
| APPROVED | <i>Carolann Wick</i> | 12/5/05 |
| | CHIEF ENGINEER | DATE |
| RECOMMENDED | <i>James M. O'Brien</i> | 11/29/05 |
| | DESIGN ENGINEER | DATE |



SECTION





ELEVATION




PLAN VIEW
SHALLOW WATER/MARSH APPLICATION

STAKED TURBIDITY CURTAIN


| | | | | |
|--|---------------------------------|---------------|-------------|---|
|  DELAWARE DEPARTMENT OF TRANSPORTATION | TURBIDITY CURTAIN | | | APPROVED <i>Carolann Wick</i> 12/5/05 <small>CHIEF ENGINEER DATE</small> |
| | STANDARD NO. E-23 (2005) | SHT. 2 | OF 2 | RECOMMENDED <i>James M. O'Brien</i> 11/29/05 <small>DESIGN ENGINEER DATE</small> |



PLAN



SECTION A-A



SECTION B-B

- NOTES:**
- 1). THE PORTABLE SEDIMENT TANK SHOWN MAY BE USED IN SITES WHERE SPACE IS LIMITED TO CONSTRUCT A DEWATERING BASIN.
 - 2). THE MAXIMUM PUMP DISCHARGE INTO THIS TYPICAL PORTABLE SEDIMENT TANK SHALL BE 425 GALLONS PER MINUTE (26 LITERS PER SECOND). THE FILTER FABRIC SHALL BE REPLACED WHEN THE PORTABLE SEDIMENT TANK CAN NO LONGER ALLOW THIS FLOW RATE, WHEN THERE IS A TEAR, OR WHEN DIRECTED BY THE ENGINEER.
 - 3). SEVERAL UN-CONNECTED OR CONNECTED IN PARALLEL PORTABLE SEDIMENT TANKS MAY BE USED WHEN A HIGHER FLOW RATE IS NEEDED TO DE-WATER THE JOB.
 - 4). OTHER DESIGNS MAY BE USED PROVIDED THE HYDRAULIC DESIGN IS SUBMITTED TO AND APPROVED BY THE STORMWATER ENGINEER.



DELAWARE
DEPARTMENT OF TRANSPORTATION

PORTABLE SEDIMENT TANK

STANDARD NO.

E-24 (2005)

SHT. 1

OF 1

APPROVED


Carolann Wick
CHIEF ENGINEER

12/5/05
DATE


RECOMMENDED

James M. O'Brien
DESIGN ENGINEER


11/29/05
DATE




INITIAL TRENCH ANCHOR DETAIL
APPLIED AT THE DOWNSTREAM END OF DITCH




TERMINAL TRENCH ANCHOR DETAIL
APPLIED AT THE UPSTREAM END OF DITCH




CHECK SLOT DETAIL
(AS NEEDED PER PLANS)




LONGITUDINAL TRENCH ANCHOR DETAIL




OVERLAP DETAIL



**STABILIZATION OF DITCHES
PLAN**





**STABILIZATION OF DITCHES
SECTION A-A**




STAPLE DETAIL

- NOTES: 1. ADDITIONAL STAPLES NOT SHOWN ARE REQUIRED AT OVERLAPS, ENDS, CHECK SLOTS AND EDGES. SEE APPROPRIATE DETAILS FOR STAPLE PLACEMENT.
2. STAPLES ARE TO BE STAGGERED.
3. TOPSOIL UNDER TURF REINFORCEMENT MAT IS TO BE TRACKED AND SEEDED.


| | | | | |
|--|--|---------------|-------------|--|
|  DELAWARE DEPARTMENT OF TRANSPORTATION | TURF REINFORCEMENT MAT APPLICATIONS | | | APPROVED <i>Carolann Wick</i> 12/5/05 CHIEF ENGINEER DATE |
| | STANDARD NO. E-25 (2005) | SHT. 1 | OF 1 | RECOMMENDED <i>James M. O'Brien</i> 11/29/05 DESIGN ENGINEER DATE |



PLAN VIEW



DETAIL B



SECTION A-A

- NOTES:
1. RIPRAP IS TO BE PLACED PRIOR TO PLACING PIPE.
 2. PLACE DELAWARE NO. 3 STONE UNDER PIPE.
 3. ELEVATION (EL.) SHOULD NOT BE HIGHER THAN PIPE INVERT.
 4. REFER TO THE PIPE ENERGY DISSIPATOR SCHEDULE ON THE CONSTRUCTION PLANS FOR THE VALUE OF DIMENSION VARIABLES.



DELAWARE
DEPARTMENT OF TRANSPORTATION

RIPRAP ENERGY DISSIPATOR DETAIL

STANDARD NO. E-26 (2006)

SHT. 1 OF 1

APPROVED *[Signature]* 10/10/06
CHIEF ENGINEER DATE
RECOMMENDED *[Signature]* 10/13/06
DESIGN ENGINEER DATE