



- NOTES**
- 1). ORANGE BANDS SHALL DESIGNATE THE LANE ASSIGNMENT. ALL LANES SHALL BE DESIGNATED FROM LEFT TO RIGHT IN THE DIRECTION OF TRAVEL. EXAMPLE: FOR A DOUBLE LEFT TURN WITH 2 THRU LANES FOR NORTHBOUND, THE CABLES WILL BE IDENTIFIED AS 1-RED W/ 1-ORANGE (LT LANE 1) 1-RED W/ 2-ORANGE (LT LANE 2), 2-RED W/ 1-ORANGE (THRU LANE 1) AND 2-RED W/ 2-ORANGE (THRU LANE 2). THIS CODE IS THEN FOLLOWED FOR THE REMAINING APPROACHES TO THE INTERSECTION.
 - 2). THE OPTICAL PRE-EMPTION DETECTOR "HOME RUN" CABLE(S) SHALL BE IDENTIFIED WITHIN THE CONTROL CABINET BY A VIOLET BAND PLUS A COLOR BAND, AS NOTED TO DENOTE THE DIRECTION OF THE DETECTOR.

☐ = SYSTEM LOOP

RED - NORTH BOUND
 YELLOW - SOUTH BOUND
 GREEN - EAST BOUND
 BLUE - WEST BOUND



LOOP DETECTOR INSTALLATION & SPLICE KIT			
STANDARD NO.	T-9 (2013)	SHT.	2 OF 3

APPROVED	SIGNATURE ON FILE <small>CHIEF ENGINEER</small>	02/14/2014 <small>DATE</small>
RECOMMENDED	SIGNATURE ON FILE <small>DESIGN ENGINEER</small>	01/14/2014 <small>DATE</small>